

DESCRIPTION

Wet Edge Extender WT900™ is a non-flammable additive with a versatile use of applications and is specifically formulated for Durable Concrete Coatings' systems. Wet Edge Extender WT900™ will help with increasing the working time and use of the product, especially at higher temperature weather conditions or when applying to large areas. The product helps to improve levelling and reduces lap marking caused by the coating drying too fast. Unlike conventional thinners, Wet Edge Extender WT900™ is a high-performance product, low odour and only needs a small quantity of product to work effectively.

FEATURES & ADVANTAGES

- Non-flammable
- Versatile application
- Low odour
- Minimal amount of product required
- Very effective
- Increases the working time
- Improves levelling
- Reduces lap marking

RECOMMENDED USE

- Water Based Epoxy WEP50 HB™
- Premium Epoxy EP100™
- Epoxy EP200™
- Polyurea PU100™
- Polyaspartic PS90™
- Urethane 2Pack™
- Durathane SP40™
- Durathane SP100™
- Aqua Urethane 2Pack™

TECHNICAL DATA & CHARACTERISTICS

APPEARANCE	Clear Liquid
COLOUR	Clear
VOLUME SOLIDS	N/A
FINISH	N/A
COVERAGE	N/A
MIX RATIO	Add 1% – 5% by volume into Durable Concrete Coatings' single pack products or into mixed two pack systems.
PACK SIZES	4L
SPECIFIC GRAVITY	0.98 kg/l
POT LIFE	N/A
DRYING TIME	N/A
RECOAT TIME	N/A
FULL CURE	N/A
SHELF LIFE	24 months, if properly stored in original unopened containers at temperatures between 10°C and 30°C and away from sunlight.

* The pot life time depends on climatic conditions and temperatures.

** Drying times generally depend on air circulation, temperature, film thickness and application methods. The figures given above are typical with good ventilation, typical film thickness and single coat application.

SURFACE PREPARATION

All surface preparations must be carried out to Australian Standard or International Standard. New concrete must be cured for a minimum of 28 days before a coating.

Concrete moisture test should be carried out prior to coating application as per Standard ASTM4263 and/ or International Standard. The moisture content should be less than 4%.

Surface to be treated must be structurally sound and the substrate compressive strength should be at least 25MPa. The substrate tensile strength should be at least 1.5N/mm². All non-structural cracks, holes and surface deformities should be repaired.

In general, the surface to be treated **MUST** be clean and free of all traces of loose material, dirt, debris, mildew, oil, grease, old coatings, curing compounds, release agents, laitance, dust and other contaminants.

All new or old concrete surfaces should be prepared by mechanical grinding, abrasive blasting, blast tracking, or any other suitable preparation/cleaning methods. Surface profile should exceed CSP 3 after preparation. Check if all traces of oil and other contaminations has been completely removed prior coating application.

For more detailed information, see following standard codes of practice, guides and techniques:

ASTM D4258 Standard practice for surface cleaning concrete for coating

ASTM D4259 Practice for abrading concrete

ASTM D4260 Practice for liquid and gelled acid etching of concrete

ASTM D4262 Test method for pH of chemically cleaned or etched concrete surfaces

ASTM D4263 Test method indicating moisture in concrete by the plastic sheet method

ASTM D4285 Test method for indicating oil or water compresses air

APPLICATION & GUIDELINES

Mixing Single Pack Systems

When using pigmented, satin or matte finish single pack systems, first thoroughly stir the single pack system base to redistribute any pigments or matting agents. Add 1% - 5% of Wet Edge Extender WT900™ by volume per litre into compatible Durable Concrete Coatings single pack products and mix thoroughly. The addition rate depends on project specific conditions such as air temperatures, substrate temperatures, product temperatures as well as air flow and relative humidity. Do NOT exceed 5% volume when adding Wet Edge Extender WT900™ to any product.

Mixing Two Pack Systems

When using pigmented, satin or matte finish two pack systems, first thoroughly stir the Part A of the two pack system base to redistribute any pigments or matting agents. Mix two pack system Part A with Part B and use a mechanical mixer to ensure thorough mixing and avoid aeration when mixing the product. Add 1% - 5% of Wet Edge Extender WT900™ by volume per mixed litre into the compatible Durable Concrete Coatings products and mix thoroughly. The addition rate depends on project specific conditions such as air temperatures, substrate temperatures, product temperatures as well as air flow and relative humidity. Do NOT exceed 5% volume when adding Wet Edge Extender WT900™ to any product.

Compatibility & Suitability

Do NOT mix this product or use this product in combination with any other products or brands. Due to the differences in substrates, material and site conditions and environmental surrounds, the applicator holds whole responsibility for checking the product's suitability for its intended purpose prior to application. Only products of the same brand/system should be used in combination as a complete system.

PRECAUTIONS

Safety Data Sheet and Technical Data Sheet must be read before using and opening this product. Keep out of reach of children. Always wear personal protective equipment (PPE) when handling this product. Keep away from heat and flame. No smoking. Provide adequate ventilation. For more details refer to safety data sheet (SDS).

Do not apply if the air or surface temperature is below 10°C, or if the temperatures is subject to drop below 10°C during applying, or after application within the curing time.

Do not apply if substrate is subject to hydrostatic pressure or rising dampness.

Do not apply if surface is subjected to unusual high temperatures above ambient temperature.

Do not apply if the surface temperature is over 30°C, or if the surface temperature is subject to raise above 30°C during applying, or after application within the curing time, or if relative humidity is suspected to become above 85%.

Do not apply if substrate is subject to rain or moisture, and protect surface at least 24 hours against any water impact, or moisture after application within the curing time. Do not use any product past its pot life. Store locked up, in a cool, dry, well ventilated place, away from sunlight, between 10°C and 30°C. Keep container tightly closed.

DISCLAIMER

Do not apply this product if there is uncertainty about its application or surface preparation. This Technical Data Sheet is to be used as a guide only; it is NOT a specification. Durable Concrete Coatings Pty Ltd has no control over the use or storage of this product and therefore does not accept liability in this regard. Any verbal advice given should not be regarded as authoritative information. This information is subject to change without notice, therefore all applicators should ensure they have current information. This product is intended for the use only of skilled tradesman and where applicable, statutory licensed tradesmen experienced and trained in the use of this product. Due to differences in substrates, application methods and local conditions purchasers of these products must ensure that it is suitable for their specific application before using these products. While the information contained in the TDS and SDS is accurate to the best of our knowledge, Durable Concrete Coatings Pty Ltd cannot guarantee that the information contained is wholly comprehensive. Subject to the provisions of the Trade Practices Act, the company's liability in relation to defective products shall be limited to replacement of the product, if the product is proven to be defective. All Durable Concrete Coatings Pty Ltd terms and conditions apply.

Durable Concrete Coatings Pty Ltd

Brisbane (07) 3808 2769 | 2/100 Kingston Road | Underwood QLD 4119

Melbourne (03) 9052 4878 | 60 Spalding Avenue | Sunshine North VIC 3020

Australia Wide 1300 800 054

info@durableconcretecoatings.com.au | www.durableconcretecoatings.com.au